



*CENTER DRAIN*

## PRODUCT SPECIFICATIONS:

- Product material - Acrylix™ surface with fiberglass composite reinforcement.
- Special installation instruction for this unit must be followed carefully.
- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Integral 1" [25mm] floor nailing flange.
- Shower Area: W- 36" [914mm] x D- 36" [914mm]
- Door Opening: W- 36" [914mm] x H- 75-3/4" [1924mm]
- Accepts Clarion Bathware Model #IN39 Dome.
- All dimensions =/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.

## 3940BF34CD

40" [1016mm] Barrier-Free Shower w/ 3/4" [19mm] Threshold & Center Drain

**Clarion**  
BATHWARE  
44 Amsler Ave.  
Shippensburg, PA 16254

Phone: (814) 226-5374  
Toll Free: (800) 576-9228  
Fax: (814) 226-0730  
www.clarionbathware.com

Signatures For Approval:

Customer: \_\_\_\_\_  
Arch./Engr: \_\_\_\_\_

Date: \_\_\_\_\_

Quote #: \_\_\_\_\_  
Job Name: \_\_\_\_\_

DWG. #

3940BF34CD -CUT

By: CAL

Date: 5/27/2021

\*\*\*IMPORTANT NOTICE\*\*\*

Clarion bathware reserves the right to change the design and/or dimensions of its products at any time. This drawing may have been updated since this publication was issued. Before placing an order for any product, refer to our website at [www.clarionbathware.com](http://www.clarionbathware.com) to obtain the most current drawings for any products that you wish to purchase. Compare the date of revision of the drawing that you have with the one on the drawing on our website. If you do not have internet access, please call your sales representative or Clarion Bathware's sales department at 1-800-576-9228.