

SOURAVIT

Ketho Mirror cabinet # KT7532



Mirror cabinet	Dimension	Weight	Order number
cIAPMO®ELECTRICAL, 2 mirror doors, 2 handles attached, 2 glass shelves, 1 sensor switch bottom right, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), Mirror cabinets require a GFCI 110 V 60 Hz power source. Flat plug will be supplied with the mirror cabinet, 2 interior lights (fluorescent tube T5 14 W 835 W)			
Colors			
M14 Terra (Decor) M18 White Matt M22 White High Gloss (Decor) M31 Pine Silver (Decor) M43 Basalt Matt (Decor) M49 Graphite Matt (Decor) M51 Pine Terra (Decor) M52 European Oak (Decor) M53 Chestnut Dark (Decor) M73 Ticino Cherry Tree (Decor) M79 Natural Walnut (Decor)			
Variant			
	39 3/8" x 7 1/8" In	ch	KT7532
Infobox			
Handles are included for optional installation on mirror glass, D minimum 3"	istance between sen	sor and reflecting surfaces =	

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.