



Mirror cabinet	Dimension	Weight	Order number
cEGS/IAPMO®*, LED dimming function, 3 mirror doors,			
shelves, 1 wooden shelf with rail cover, 1 cosmetic mirr sensor switch bottom right, LED (life span > 30,000 hou			
module permanently enclosed, GFCI outlets are not sup			
the manufacturer (GFCI outlets can be added to the cabi	inet by a		
certified electrician on the job site), mirror cabinets req			
GFCI 110 V 60 Hz power source, flat plug will be supplie the mirror cabinet, LED module 3500 kelvin light color,			
the mirror cabinet, LED modute 3300 ketvin tight cotor,	ZZ Watt		
Colors			
M00			
Variant			
	47 1/4" x 5 3/4" I	nch	VE750400000
Infobox			
Distance between sensor and reflecting surfaces = mini CSA C22.2 No. 12-1982	mum 3", * Complies with fo	llowing standards: UL 9	62 and
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709
	, -		

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.